

DELL PowerEdge T430 server 300 GB Tower (5U) Intel® Xeon® E5 v4 E5-2620V4 2,1 GHz 8 GB DDR4-SDRAM

Brand : DELL **Product family:** PowerEdge **Product code:** T430-0855ROKDA

Product name: T430

16x 2.5", Intel Xeon E5-2620 v4 (20M Cache, 2.10 GHz), 8GB, 300GB, PERC H330, DVD+/-RW, iDRAC 8 Express + ROK Datacenter

DELL PowerEdge T430. Processor family: Intel® Xeon® E5 v4, Processor frequency: 2,1 GHz, Processor model: E5-2620V4. Internal memory: 8 GB, Internal memory type: DDR4-SDRAM. Total storage capacity: 300 GB. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Optical drive type: DVD±RW. Chassis type: Tower (5U)





Processor		Network	
Processor manufacturer *	Intel	Cabling technology	10/100/1000Base-T(X)
Processor family *	Intel® Xeon® E5 v4	Ethernet interface type	Gigabit Ethernet
Processor model *	E5-2620V4	Ports & interfaces	
Processor frequency *	2,1 GHz	Ethernet LAN (RI-45) ports *	2
Processor boost frequency	3 GHz	USB 2.0 ports quantity	6
Processor cores	8	USB 3.2 Gen 1 (3.1 Gen 1) Type-A	
Processor cache	20 MB	ports quantity	2
Motherboard chipset	Intel C610	VGA (D-Sub) ports quantity	1
Memory channels supported by processor	Quad	Serial ports quantity	1
Number of processors installed	1	Expansion slots	
Thermal Design Power (TDP)	85 W	PCI Express x1 (Gen 2.x) slots	1
Processor cache type	Smart Cache	PCI Express x8 (Gen 3.x) slots	2
System bus rate	8 GT/s	PCI Express x16 (Gen 3.x) slots	2
Maximum number of SMP processors	2	PCI Express slots version	3.0
Compatible processor series	Intel® Xeon®	Design	
Processor socket	LGA 2011-v3	Chassis type *	Tower (5U)
Processor lithography	14 nm	Performance	
Processor threads	16	Trusted Platform Module (TPM)	✓
Processor operating modes	64-bit	Trusted Platform Module (TPM)	
Stepping	R0	version	1.2
Bus type	QPI	Software	
Number of QPI links	2	Softman C	Windows Conver 2009 CD2 (v96/v64)
Processor codename	Broadwell		Windows Server 2008 SP2 (x86/x64) Windows Server 2012 SP2 (x86/x64) Windows Server 2008 R2 (x64) Windows Server 2012 R2 (x64) Novell SUSE Linux Enterprise Server Red Hat Enterprise Linux VMware vSphere
Tcase	74 °C		
Maximum internal memory supported by processor	1,54 TB	Compatible operating systems *	
Memory types supported by processor	DDR4-SDRAM		
Memory clock speeds supported by processor	1600,1866,2133 MHz	Processor special features	
Memory bandwidth supported by processor (max)	68,3 GB/s	CPU configuration (max) Enhanced Intel SpeedStep	2
ECC supported by processor		Technology	•
"	•	Intel® Identity Protection	×
Execute Disable Bit	✓	Technology (Intel® IPT)	

Processor		Processor special features	
Idle States	*	Intel Virtualization Technology for Directed I/O (VT-d)	✓
Thermal Monitoring Technologies Maximum number of PCI Express	40	Intel® Hyper Threading Technology (Intel® HT Technology)	✓
lanes Processor package size Supported instruction sets Processor code	45 x 52.5 mm AVX 2.0 SR2R6	Intel® Turbo Boost Technology Intel Flex Memory Access	2.0 x
		Intel® AES New Instructions (Intel® AES-NI)	· ·
Scalability Physical Address Extension (PAE)	2S •	Intel Trusted Execution Technology	✓
Physical Address Extension (PAE) Embedded options available	46 bit	Intel Enhanced Halt State Intel VT-x with Extended Page	✓ ✓
Processor series	Intel Xeon E5-2600 v4	Tables (EPT) Intel Demand Based Switching	1
Conflict-Free processor	✓	Intel® Secure Key	✓
Memory		Intel TSX-NI	✓
Internal memory *	8 GB	Intel® OS Guard	✓
Internal memory type *	DDR4-SDRAM	Intel 64	✓
Memory slots ECC	12 ✓	Intel Identity Protection Technology version	0,00
Memory clock speed	2133 MHz	Intel Secure Key Technology version	1,00
Maximum internal memory *	384 GB	Intel Virtualization Technology (VT-x)	✓
Storage		Intel TSX-NI version	1,00
Total storage capacity *	300 GB	Processor ARK ID	92986
Number of hard drives installed Supported HDD sizes	1 2.5"	Operational conditions	
RAID support * RAID levels Hot-Plug support Optical drive type * Internal drive bays	2.5° 0, 1, 5, 6, 10, 50 DVD±RW 16	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	10 - 35 °C -40 - 65 °C 10 - 80% 5 - 95% 0 - 3048 m 0 - 12000 m
Graphics		Weight & dimensions	
Maximum graphics card memory	16 MB	Width	430,2 mm
Network		Depth	584 mm
Ethernet LAN	✓	Height	444,3 mm

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.